

KALKASKA COUNTY ROAD COMMISSION

SPECIAL PROVISION
FOR
HOT MIX ASPHALT CRACK TREATMENT

JSLR

1 of 1

05/14/20

Description. The work consists of treating cracks in hot mix asphalt (HMA) surfaces using either a saw or rout and seal process or an overband process.

Materials. Provide materials in accordance with subsection 502.02 of the 2012 Standard Specifications for Construction with the following modifications:

1. Delete subsection 502.02.B.1 of the 2012 Standard Specifications for Construction and replace with the following: "Performance graded asphalt binder PG 58 -28 or PG 68 -28."
2. Add the following to the first sentence in subsection 502.02.B.2 of the 2012 Standard Specification for Construction: "and also meets ASTM D6690 Type II."

Construction. Ensure all construction is in accordance with subsection 502.03 of the 2012 Standard Specifications for Construction with the following modifications:

1. Delete the second sentence of the second paragraph of subsection 502.03.D.2 of the 2012 Standard Specifications for Construction and replace with the following: "Apply overband 4 inches wide, \pm 1/4 inch and from 1/8 inch to 3/16 inch thick.
2. Add the following to the end of subsection 502.03.D.2.c of the 2012 Standard Specifications for Construction: "Allow curing for a minimum of 7 days prior to placement of chip seal."

Measurement and Payment.

Pay Item

Pay Unit

Overband Crack Fill, Roadbed

Per Pound